

ULTRA 2K POLYESTER PUTTY - UCF.100

ULTRA 2K POLYESTER PUTTY

UCF.100

FEATURES:

Easy sanding properties

Excellent corrosion resistance

Excellent coverage

Excellent adhesion

Eliminates sinkage

MADE IN CANADA

ULTRA 2K is a unique, stain resistant, smooth spreading polyester glazing putty, ideally suited for applications in areas vulnerable to stress. It offers excellent corrosion resistance and adhesion to bare steel, galvanized steel, aluminum, SMC, and over OEM paint on plastic bumpers. Advanced lightweight formula makes sanding effortless and superb feather edge.

ULTRA 2K POLYESTER PUTTY - UCF.100


TECHNICAL INFORMATION

PREPARATION:



- Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent. Thoroughly dry the surface before repairing.
- Use 80-180 grit to remove or scuff the paint and featheredge.

MIXING:



- Place the desired amount of material on a clean, non-fibrous surface. Knead the cream hardener before use.
- Hardener 2% by weight.
- Mix thoroughly until uniform color is achieved.
- Approximate setting time is 6 - 7 minutes @ 20°C

APPLICATION:



- Spread a thin layer of mixed material over surface using firm pressure.
- Apply additional layers to build material slightly higher than the surface to allow for sanding to desired contour

FINISH:



- Sand as necessary with 180 grit sandpaper.
- Feather edge with 180 then 220-320 grit if desired.

TOPCOAT:



- Any 2K Primer, 2K epoxy, or 1K primer as per manufacturer's specs.