

ULTRASPLOOCH LIGHTWEIGHT BODY FILLER - UCF.200

ULTRASPLOOCH LIGHTWEIGHT BODY FILLER



FEATURES:

Smooth spreading

Easy sanding properties

Excellent corrosion resistance

Excellent coverage

Excellent adhesion

Eliminates sinkage

MADE IN CANADA

ULTRASPLOOCH is a tack free, lightweight body filler designed to reduce sandpaper clogging and sand to a fine finish. May be applied directly to galvanized metal, aluminum, bare steel and for cosmetic repairs to fibreglass and some composites. Stain resistant for use under basecoat/clearcoat repairs. Body damage up to 1/4" (6 mm) in depth can be repaired with ULTRASPLOOCH.

ULTRASPLOOCH LIGHTWEIGHT BODY FILLER - UCF.200


TECHNICAL INFORMATION

PREPARATION:



- Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent. Thoroughly dry the surface before repairing.
- Use 40-80 grit to remove or scuff the paint and featheredge.

MIXING:



- Place the desired amount of material on a clean, non-fibrous surface. Knead the cream hardener before use.
- Hardener 2% by weight.
- Mix thoroughly until uniform color is achieved.

APPLICATION:



- Spread a thin layer of mixed material over surface using firm pressure.
- Apply additional layers to build material slightly higher than the surface to allow for sanding to desired contour

NOTE: Do not apply over new or uncured coatings. Avoid thick heavy applications.

FINISH:



- Sand rough shape as necessary with 40-80 grit sandpaper.
- Use 80 grit sandpaper to sand the filler and featheredge and final repair with 180 grit sandpaper.

TOPCOAT:



- Any 2K Primer, 2K epoxy, or 1K primer as per manufacturer's specs.